

Decorative
Sydney Concretors Warehouse Pty Ltd

Cnr Elizabeth St. & Hargraves Place, Wetherill Park, NSW 2164

PO Box 6600, Wetherill Park NSW 2164

Email: sydney_concretors@bigpond.com Website: www.concretorswarehouse.com

Telephone: (02) 9756 4688 Mobile: 0409 996 899 Fax: (02) 9756 4866

Technical Data

Sydney Decorative Concretors Warehouse **High Gloss Concrete Sealer** (Applies to Clear or Tinted)

For Professional Use Only

Description: SDCW High Gloss Sealer provides a clear glossy film to protect decorative concrete such as stamped, stencilled and spray on finishes and can be applied to many other cementitious surfaces.

Packaging: 5L, 10L, 20L and 200L Drums.

Use: SDCW High Gloss Sealer seals and helps protect concrete from the penetration of dirt and grime. It also helps protect the concrete from weathering and as a moisture barrier.

SDCW High Gloss can also be tinted to provide a solid colour seal over plain concrete surfaces or to change the colour of existing surfaces.

Application: New Concrete: Ensure concrete is sufficiently cured (minimum 14 days), clean and free from grease and oil. A pressure clean at 3000psi should be sufficient to achieve this. However an acid wash may be required to remove any loose cement residue. This also provides for better surface adhesion.
 Allow to completely dry before sealing.

Old Concrete: Will require cleaning to remove any substance which could affect adhesion. eg. Paint, algae, mould, or oil. This again achieved by pressure cleaning. Allow to completely dry before applying sealer.

This sealer has been formulated to be applied as a top coat sealer ensuring maximum strength and shine. If a 1st coat / prime coat required refer to SDCW Trade Sealer.

Applied with a solvent resistant soft broom or by paint roller.

Usage rate: 1 x 20L drum covers approximately 80-100m², depending on porosity.

Decorative
Sydney^ Concretors Warehouse Pty Ltd

Cnr Elizabeth St. & Hargraves Place, Wetherill Park, NSW 2164

PO Box 6600, Wetherill Park NSW 2164

Email: sydney_concretors@bigpond.com Website: www.concretorswarehouse.com

Telephone: (02) 9756 4688 Mobile: 0409 996 899 Fax: (02) 9756 4866

Features: Ease of application, fast drying and clear film. Readily maintained with Hi Gloss sealer for subsequent coats for maximum gloss finish (You would expect to reseal a domestic driveway every 1 -3 years).

Specifications:

Solids:	22 % +/- 2%
Ultra Violet light:	Highly Resistant and Stable
Application Rate:	4-5m ² per L
Appearance:	Clear Liquid

Precautions: Not for food preparation areas. It is not recommended to seal at extreme temperatures (below 8°C or above 30°C).

After sealing it is recommended that the sealed surface be protected from:

- Foot traffic for a minimum 24hrs
- Vehicle traffic for a minimum of 48hrs.

Highly flammable, therefore, use in a well ventilated area. Do not allow contact with the skin or eyes. Do not breathe vapours. Mask, gloves, goggles, boots and other protective clothing must be worn. Before using read MSDS on this product.

Limitations: SDCW has no control over the use or storage of this product and cannot accept any liability in this regard. This product is intended for professional use only.